

Order Code:
JM-352C



Key Features

- Multi function inverter: MIG/MAG/MMA and gasless, flux cored, lift arc TIG
- Digital display
- 4 roll feed drive
- High duty cycle
- Advanced control circuitry
- Suitable for 0.8, 1.0 and 1.2mm wire
- Stable welding arc with minimal spatter
- Burn back control
- Spool gun interface
- Wire inching feature
- VRD on MMA setting

Technical Data

Input Voltage	AC 400V - 50/60 Hz
Ieff(A)	13.7
Input Power (kVA)	15
Voltage Adjustment Range (V)	15 - 38
Current Range (A)	50 - 350
Duty Cycle @ 40°C	350A @ 40%
No-Load Voltage (V)	(19V - VRD)
Wire Spool Size	ø 300mm
Efficiency (%)	85
Power Factor	0.93
Protection/Insulation Class	IP21S/F
Dimensions (LxWxH mm)	900 x 450 x 755
Weight (Kg)	52

*5 year warranty subject to product registration



Accommodates full size gas cylinder



Consistently reliable performance for highly demanding and repetitive weld cycles

Optional

Spool Gun
Order Code:
JSG-02



MMA Leads

Order Code:
WCS25-3WEL



Includes
MIG torch, gas regulator, work return lead & clamp